

L940 AU Series

Infrared LED Lamp

This series of L940-__AU is a GaAs LED mounted on a lead frame and encapsulated in various types of epoxy lens which offer different design settings.

On forward bias, it emits a high power radiation of typical 17mW with a peak wavelength at 940nm.

Specifications

- | | |
|--------------------|-------------|
| 1. Chip material | GaAs |
| 2. Peak wavelength | 940nm |
| 3. Resin Material | Epoxy resin |
| 4. Solder | Lead free |



Absolute Maximum Ratings

Item	Symbol	Maximum Rated Value	Unit	Ambient Temperature
Power Dissipation	P_D	160	mW	$T_a=25^{\circ}\text{C}$
Forward Current	I_F	100	mA	$T_a=25^{\circ}\text{C}$
Pulse Forward Current	I_{FP}	1000	mA	$T_a=25^{\circ}\text{C}$
Reverse Voltage	V_R	5	V	$T_a=25^{\circ}\text{C}$
Operating Temperature	T_{OPR}	-30 ~ +85	$^{\circ}\text{C}$	$T_a=25^{\circ}\text{C}$
Storage Temperature	T_{STG}	-40 ~ +100	$^{\circ}\text{C}$	
Soldering Temperature	T_{SOL}	265	$^{\circ}\text{C}$	

Electro-Optical Characteristics ($T_a=25^{\circ}\text{C}$)

Item	Symbol	Condition	Minimum	Typical	Maximum	Unit
Forward Voltage	V_F	$I_F=50\text{mA}$		1.3	1.5	V
Reverse Current	I_R	$V_R=5\text{V}$			10	μA
Total Radiated Power	P_O	$I_F=50\text{mA}$	12	17		mW
Peak Wavelength	λ_P	$I_F=50\text{mA}$		940		nm
Half Width	$\Delta\lambda$	$I_F=50\text{mA}$		50		nm
Rise Time	t_r	$I_F=50\text{mA}$		2500		ns
Fall Time	t_f	$I_F=50\text{mA}$		1000		ns

Characteristics of Radiant Intensity (Ta=25°C)

Type	Viewing Half Angle	Radiant Intensity I _F =50mA Unit : mW/sr			Outer Dimension	Dimension Figure
		Minimum	Typical	Maximum		
L940-01AU	±10°		50		Φ 5	1
L940-02AU	±7°		75		Φ 5	2
L940-03AU	±10°		50		Φ 5	3
L940-04AU	±20°		20		Φ 5	4
L940-05AU	±40°		7		Φ 5	5
L940-06AU	±7°		80		Φ 5	6
L940-09AU	±25°(Long) ±15°(Short)		30		Φ 5 Oval	7
L940-46AU					Φ 5	8
L940-41AU	±16°		30		Φ 4	9
L940-42AU	±23°		25		Φ 4	10
L940-31AU					Φ 3	11
L940-33AU	±18°		20		Φ 3	12
L940-34AU					Φ 3	13
L940-36AU	±33°		10		Φ 3	14

Brightness is measured by Tektronix J-16
 Total Radiant Power is measured by Photodyne #500


Outer Dimension of LED Lamp (1/2)

<p>Figure-1 Φ 5Mold (Type01)</p> <p>cup position 4.7 1.5max</p> <p>ϕ 5.8\pm0.2 ϕ 5\pm0.2</p> <p>9\pm0.2 21 min. 1 typ. Cathode</p> <p>1.0\pm0.2 Anode 2-0.5sq\pm0.1</p>	<p>Figure-2 Φ 5Mold (Type02)</p> <p>cup position 5.32 1.5max</p> <p>ϕ 5.8\pm0.2 ϕ 5.2\pm0.2</p> <p>8.5\pm0.2 21 min. 1 typ. Cathode</p> <p>1.0\pm0.2 Anode 2-0.5sq\pm0.1</p>
<p>Figure-3 Φ 5Mold (Type03)</p> <p>cup position 4.55 1.5max</p> <p>ϕ 5.8\pm0.2 ϕ 5\pm0.2</p> <p>8.25\pm0.2 21 min. 1 typ. Cathode</p> <p>1.0\pm0.2 Anode 2-0.5sq\pm0.1</p>	<p>Figure-4 Φ 5Mold (Type04)</p> <p>cup position 3.55 1.5max</p> <p>ϕ 5.8\pm0.2 ϕ 5\pm0.2</p> <p>7.7\pm0.2 21 min. 1 typ. Cathode</p> <p>1.0\pm0.2 Anode 2-0.5sq\pm0.1</p>
<p>Figure-5 Φ 5Mold (Type05)</p> <p>cup position 0.55 1.5max</p> <p>ϕ 5.4\pm0.2 ϕ 4.8\pm0.2</p> <p>3.35 21 min. 1 typ. Cathode</p> <p>ϕ 4.45\pm0.2 Anode 1.0\pm0.2 2-0.5sq\pm0.1</p>	<p>Figure-6 Φ 5Mold (Type06)</p> <p>cup position 5.6 1.5max</p> <p>ϕ 5.5\pm0.2</p> <p>8.7\pm0.2 21 min. 1 typ. Cathode</p> <p>Anode 2-0.5sq\pm0.1</p>
<p>Figure-7 Φ 5Mold (Type09)</p> <p>cup position 4.1 1.5max</p> <p>4.7\pm0.2 5.5\pm0.2</p> <p>7.7\pm0.2 21 min. 1 typ. Cathode</p> <p>Anode 2-0.5sq\pm0.1</p>	<p>Figure-8 Φ 5Mold (Type46)</p> <p>1.5max</p> <p>5.8\pm0.2 4.8\pm0.2</p> <p>4.4\pm0.2 21 min. 1 typ. Cathode</p> <p>0.6 Anode 2-0.5sq\pm0.1</p>
<p>Figure-9 Φ 4Mold (Type41)</p> <p>cup position 3.05 1max</p> <p>4.7\pm0.2 ϕ 3.9\pm0.2</p> <p>6.45\pm0.2 21 min. 1 typ. Cathode</p> <p>1.5\pm0.2 Anode 2-0.5sq\pm0.1</p>	<p>Figure-10 Φ 4Mold (Type42)</p> <p>cup position 3.05 1max</p> <p>4.7\pm0.2 ϕ 3.9\pm0.2</p> <p>6.45\pm0.2 21 min. 1 typ. Cathode</p> <p>1.5\pm0.2 Anode 2-0.5sq\pm0.1</p>



Outer Dimension of LED Lamp (2/2)

<p>Figure-11 $\Phi 3$Mold (Type31)</p> <p>cup position</p> <p>0.37 1max</p> <p>$\phi 3.6 \pm 0.2$</p> <p>3.5 ± 0.2 21 min. Cathode 1 typ.</p> <p>1.5 typ. Anode 2-0.5sq ± 0.1</p>	<p>Figure-12 $\Phi 3$Mold (Type33)</p> <p>cup position</p> <p>2.65 1max</p> <p>$\phi 3.8 \pm 0.2$</p> <p>$\phi 3 \pm 0.2$ 5.3 21 min. Cathode 1 typ.</p> <p>0.8 typ. Anode 2-0.5sq ± 0.1</p>
<p>Figure-13 $\Phi 3$Mold (Type34)</p> <p>cup position</p> <p>3.25 1max</p> <p>$\phi 3.8 \pm 0.2$</p> <p>$\phi 3 \pm 0.2$ 5.3 ± 0.2 21 min. Cathode 1 typ.</p> <p>1.5 typ. Anode 2-0.5sq ± 0.1</p>	<p>Figure-14 $\Phi 3$Mold (Type36)</p> <p>cup position</p> <p>2.1 1max</p> <p>$\phi 4 \pm 0.2$</p> <p>$\phi 3 \pm 0.2$ 5.3 ± 0.2 21 min. Cathode 1 typ.</p> <p>2 ± 0.4 Anode 2-0.5sq ± 0.1</p>
<p>Figure-15</p>	<p>Figure-16</p>
<p>Figure-17</p>	<p>Figure-18</p>
<p>Figure-19</p>	<p>Figure-20</p>





The Viewing half angle (1/2)







The Viewing half angle (2/2)

<p>Figure-11 Φ 3Mold (Type31)</p>	<p>Figure-12 Φ 3Mold (Type33)</p> 
<p>Figure-13 Φ 3Mold (Type34)</p>	<p>Figure-14 Φ 3Mold (Type36)</p> 
<p>Figure-15</p>	<p>Figure-16</p>
<p>Figure-17</p>	<p>Figure-18</p>
<p>Figure-19</p>	<p>Figure-20</p>


L940 AU series Operating Characteristics (1/2)



L940 AU series Operating Characteristics (2/2)



Recommended Land Layout



Soldering Conditions

